

OxBox Inline Serial Digital Ground Isolator



Key Features

- In line cable isolator
- SDI and HDTV versions
- Small size
- No power supply needed
- Fast and simple to install
- Suitable for fixed and temporary circuits
- Low cost

These simple low cost devices have been designed to provide signal isolation, eliminating group loop effects, for example, often associated with fixed and temporary installations. Both SDI and HDTV versions are available.

This equipment is part of the company's extensive range of practical low cost solutions. For choices and convenience alternative products, choices may be available in the Micro, Mini, Midi and Maxi services for broadcast and professional applications. We are continually adding new products and would welcome your thoughts and suggestions.

Specifications

General	
Video	SDI up to 360 Mb/s / SMPTE 259M / 525/625 (SDI version)
Return Loss	> 15dB up to 360 MHz
Impedance	75 ohm
Frequency range	0,4-800 MHz
Insertion loss	< 0,6 dB at 270 MHz < 1 dB at 360 MHz
Physical	
Weight	200g
Dimensions	40x25x25mm

Ordering Information

GI01 - OxBox Inline Serial Digital Ground Isolator

The above information is subject to continual change due to product development.
Oxygen DCT 2009 E & OE

OxBox Inline Serial Digital Ground Isolator



Key Features

- In line cable isolator
- SDI and HDTV versions
- Small size
- No power supply needed
- Fast and simple to install
- Suitable for fixed and temporary circuits
- Low cost

These simple low cost devices have been designed to provide signal isolation, eliminating group loop effects, for example, often associated with fixed and temporary installations. Both SDI and HDTV versions are available.

This equipment is part of the company's extensive range of practical low cost solutions. For choices and convenience alternative products, choices may be available in the Micro, Mini, Midi and Maxi services for broadcast and professional applications. We are continually adding new products and would welcome your thoughts and suggestions.

Specifications

General	
Video	SDI up to 360 Mb/s / SMPTE 259M / 525/625 (SDI version)
Return Loss	> 15dB up to 360 MHz
Impedance	75 ohm
Frequency range	0,4-800 MHz
Insertion loss	< 0,6 dB at 270 MHz < 1 dB at 360 MHz
Physical	
Weight	200g
Dimensions	40x25x25mm

Ordering Information

GI01 - OxBox Inline Serial Digital Ground Isolator

The above information is subject to continual change due to product development.
Oxygen DCT 2009 E & OE